

**BB HOOP PINE EXTERIOR MULTIPLY PLYWOOD AS/NZS 2271****PRODUCT SPECIFICATIONS**

<b>Product:</b>	B/B HOOP PINE EXTERIOR MULTIPLY PLYWOOD
<b>Veneer Grade:</b>	B Grade (Face) and B Grade (Back)
<b>Standard:</b>	AS/NZS 2271:2004 Plywood for exterior use
<b>Manufacturer:</b>	Austral Plywoods – Australian Grown & Made
<b>Product Certification:</b>	Engineered Wood Product Association of Australasia (EWPA) JAS-ANZ
<b>Environmental Certification:</b>	Responsible Wood/PEFC AS4707:2014 Chain of Custody for Forest Based Products
<b>Veneer Timber Species:</b>	Hoop Pine (Araucaria Cunninghamii)
<b>Core Timber Species:</b>	Hoop Pine (Araucaria Cunninghamii)
<b>Sheet Size:</b>	2400 x 1200mm
<b>Thicknesses:</b>	4mm, 5, 6.5, 9, 12, 15, 18, 24, 30mm
<b>Density:</b>	600kgs/m <sup>3</sup> (approx.)
<b>Glue Bond:</b>	Permanent Type “A” Bond (Phenolic Resin)
<b>Formaldehyde:</b>	Emission “Super E0”
<b>Applications:</b>	Where strength & durability and decent appearance are required such as in home projects, construction, manufacturing, furniture making & cabinetry (not recommended for doors).

**PRODUCT DESCRIPTION**

BB plywood with face & back veneers exhibiting a more natural appearance including characteristics such as colour variation, filled splits and swirling grain. Suitable for various applications being a durable marine timber species with structural rating. However not generally recommended for high-end clear staining, it's better suited for a liming white coating or equivalent for appearance. In addition, it has high grade 1.5mm core veneers, creating an even and aesthetic edge with a black glue.

**Finishing**

In semi exposed exterior applications, the product must be adequately protected by the use of a suitable water based, exterior paint or stain on both sides of the sheet & edges, irrespective of whether the sides are exposed to the weather or not. It's recommended to contact a reputable paint supplier and follow the manufacturer's instructions. Do not use oil-based products on this plywood as oil-based paints or stains may penetrate the surface veneer of the plywood and react with adhesives that bond the core veneers together. No warranty or guarantee is offered by Plywood & Panel Supplies Pty Ltd (PPS) if oil-based paint or stain has been applied to the plywood. This plywood is not suitable for use in the manufacture of doors and no warranty/ guarantee is offered by PPS if this plywood is utilised in any application associated with the manufacture of doors.

**Disclaimer**

The information provided herein is believed to be accurate but is not warranted to be, whether it originated with PPS or not. This information cannot be warranted by PPS to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances. Always refer to manufacturers span tables for correct loadings.