PLYWOOD + PANEL

www.plywoodandpanel.com.au

P +61 7 3279 7111 **E** info@plywoodandpanel.com.au

MDF STANDARD

PRODUCT SPECIFICATIONS

Product:MDF STANDARD (STD)Finish:Smooth Sanded Fine FinishManufacturer:Laminex – Trade Essentials

Standard: AS/NZS 1859.2 Environmental Certification: Green Tag Certified

Core Timber Species: Renewable Plantation Pine

Sheet Size: 2400 x 1200mm, 2400 x 1800mm, 2700 x 1200mm, 3600 x

1200mm, 3600 x 1800mm

Thicknesses: 3, 6, 9, 12, 16, 18, 25, 32mm

Density: 700-760kgs/m³ (approx.)

Glue Bond: Urea Formaldehyde Resin

Formaldehyde: Emission "E0"

Applications: Substrates, packing protection, shelving, joinery, linings &

partitions

PRODUCT DESCRIPTION

Medium Density Fibreboard (MDF), a compressed wood particle fibreboard that is suitable for interior use or one-off exterior use applications. For applications involving high humidity or damp conditions MDF Moisture Resistant is better suited.

* Australian manufactured MDF is slightly oversized such as $2420 \times 1213 \text{mm}$ or $3630 \times 1213 \text{mm}$ and may change with a change in manufacturer. Please measure exact width of sheets for setting out wall frames and if there are changes in the colour of the MDF this may result in a change in size such as $2415 \times 1207 \text{mm}$.

Disclaimer

The information provided herein is believed to be accurate but is not warranted to be, whether it originated with PPS or not. This information cannot be warranted by PPS to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances. Always refer to manufacturers span tables for correct loadings.