

## WHITE MELAMINE MOISTURE RESISTANT MDF

### PRODUCT SPECIFICATIONS

<b>Product:</b>	WHITE MELAMINE MDF MOISTURE RESISTANT (MR)
<b>Finish:</b>	Satin
<b>Manufacturer:</b>	Laminex – Trade Essentials
<b>Standard:</b>	AS/NZS 1859.2
<b>Environmental Certification:</b>	Green Tag Certified
<b>Core Timber Species:</b>	Renewable Plantation Pine
<b>Sheet Size:</b>	2400 x 1200mm, 3600 x 1200mm
<b>Thicknesses:</b>	16, 18mm
<b>Density:</b>	730kgs/m <sup>3</sup> (approx.)
<b>Glue Bond:</b>	Melamine Urea Formaldehyde (MUF)
<b>Formaldehyde:</b>	Emission “E0”
<b>Applications:</b>	Interior cabinetry, kitchen cupboards, bathroom vanities, laundry cupboards, shelving and wall linings

### PRODUCT DESCRIPTION

Moisture Resistant Medium Density Fibreboard (MDF) a compressed wood particle fibreboard with a non-porous & hardwearing white melamine pressed on both sides. This is suitable for areas of high humidity and damp conditions. The satin finish makes it ideal for 2-pack polyurethane coating systems as supplied by trade-trade professionals.

*\* Australian manufactured MDF is slightly oversized such as 2420 x 1213mm or 3630 x 1213mm and may change with a change in manufacturer. Please measure exact width of sheets for setting out wall frames and if there are changes in the colour of the MDF this may result in a change in size such as 2415 x 1207mm.*

#### Disclaimer

The information provided herein is believed to be accurate but is not warranted to be, whether it originated with PPS or not. This information cannot be warranted by PPS to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is correct, applicable and suitable to their circumstances. Always refer to manufacturers span tables for correct loadings.